

SAFETY DATA SHEET



SP2198 MS Hardener Medium

Section 1. Identification

Product identifier : SP2198 MS Hardener Medium
Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Use in coatings - Hardener.

Supplier's details

Manufacturer : Valspar b.v.
Zuiveringweg 89
8243 PE Lelystad
The Netherlands
tel: +31 (0)320 292200
fax: +31 (0)320 292201

valspar

Emergency telephone number : Call: +31 (0)320 292200 (during daytime)

Supplier : Valspar Automotive Australia Pty Limited
Unit 11/8 Kerta Road
Kincumber NSW 2251
AUSTRALIA
T: +612 43684054
F: +612 43684215
www.valsparautomotive.com.au

Emergency telephone number : Poisons Information Centre: Australia 131 126

Section 2. Hazard(s) identification

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 3
SKIN SENSITISATION - Category 1
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Respiratory tract irritation) - Category 3
ASPIRATION HAZARD - Category 1
LONG-TERM AQUATIC HAZARD - Category 3

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : Flammable liquid and vapour.
May cause an allergic skin reaction.
May be fatal if swallowed and enters airways.
May cause respiratory irritation.
Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention : Wear protective gloves. Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Avoid release to the environment.

Section 2. Hazard(s) identification

- Response** : IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
- Storage** : Store locked up. Store in a well-ventilated place. Keep cool.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Supplemental label elements** : Not applicable.

Other hazards which do not result in classification : None known.

Section 3. Composition and ingredient information

Substance/mixture : Mixture

Ingredient name	% (w/w)	CAS number
2-methoxy-1-methylethyl acetate	≥30 - ≤60	108-65-6
Aliphatic polyisocyanate.	≥10 - ≤30	28182-81-2
n-butyl acetate	≥10 - ≤15	123-86-4
Aliphatic polyisocyanate 2.	≤10	53880-05-0
xylene	≤8.5	1330-20-7
Solvent naphtha (petroleum), light arom.	≤4.9	64742-95-6
1,2,4-trimethylbenzene	≤3	95-63-6
ethylbenzene	≤2	100-41-4

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Section 4. First aid measures

Ingestion : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye irritation.
Inhalation : May cause respiratory irritation.
Skin contact : Causes skin irritation. May cause an allergic skin reaction.
Ingestion : May be fatal if swallowed and enters airways.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:
 pain or irritation
 watering
 redness

Inhalation : Adverse symptoms may include the following:
 respiratory tract irritation
 coughing

Skin contact : Adverse symptoms may include the following:
 irritation
 redness

Ingestion : Adverse symptoms may include the following:
 nausea or vomiting

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

Section 5. Firefighting measures

- Specific hazards arising from the chemical** : Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapour/gas is heavier than air and will spread along the ground. Vapours may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- Hazchem code** : •3Y

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not swallow. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls and personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
2-methoxy-1-methylethyl acetate	Safe Work Australia (Australia, 1/2014). Absorbed through skin. TWA: 50 ppm 8 hours. TWA: 274 mg/m ³ 8 hours. STEL: 100 ppm 15 minutes. STEL: 548 mg/m ³ 15 minutes.
Aliphatic polyisocyanate.	Safe Work Australia (Australia, 1/2014). Skin sensitiser. STEL: 0.07 mg/m ³ , (as -NCO) 15 minutes. TWA: 0.02 mg/m ³ , (as -NCO) 8 hours.
n-butyl acetate	Safe Work Australia (Australia, 1/2014). STEL: 950 mg/m ³ 15 minutes. STEL: 200 ppm 15 minutes. TWA: 713 mg/m ³ 8 hours. TWA: 150 ppm 8 hours.
xylene	Safe Work Australia (Australia, 1/2014). STEL: 655 mg/m ³ , 0 times per shift, 15 minutes. STEL: 150 ppm, 0 times per shift, 15 minutes. TWA: 350 mg/m ³ , 0 times per shift, 8 hours. TWA: 80 ppm, 0 times per shift, 8 hours.
1,2,4-trimethylbenzene	Safe Work Australia (Australia, 1/2014). TWA: 123 mg/m ³ 8 hours. TWA: 25 ppm 8 hours.

Section 8. Exposure controls and personal protection

ethylbenzene

Safe Work Australia (Australia, 1/2014).STEL: 543 mg/m³ 15 minutes.

STEL: 125 ppm 15 minutes.

TWA: 434 mg/m³ 8 hours.

TWA: 100 ppm 8 hours.

- Appropriate engineering controls** : Use only with adequate ventilation. Use spray booth. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment. The spray booth must be designed, constructed, installed and maintained in accordance with AS/NZS 4114.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
- Individual protection measures**
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. Recommended: If inhalation hazards exist, a full-face respirator may be required instead.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): Recommended EN 374 butyl rubber polyvinyl alcohol (PVA) Viton® ≥ 0.7 mm
4 - 8 hours (breakthrough time): Recommended EN 374 neoprene ≥ 0.7 mm
< 1 hour (breakthrough time): Conditionally suitable materials for protective gloves; EN 374: Nitrile rubber - NBR (≥ 0.35 mm). Only suitable as splash protection. Only suitable for brief exposure. In the event of contamination, change protective gloves immediately.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Recommended: Cotton or cotton/synthetic overalls or coveralls are normally suitable.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: full-face mask supplied-air respirator.

Section 9. Physical and chemical properties

Appearance

Physical state	: Liquid.
Colour	: Clear.
Odour	: Not available.
Odour threshold	: Not available.
pH	: Not available.
Melting point	: Not available.
Boiling point	: >100°C (>212°F)
Flash point	: Closed cup: 35°C (95°F)
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Lower: 1.2% Upper: 10.8%
Vapour pressure	: Not available.
Vapour density	: 4.3 [Air = 1]
Relative density	: 1.005
Solubility	: Insoluble in the following materials: cold water and hot water.
Partition coefficient: n-octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (40°C (104°F)): 0.04 cm ² /s (4 cSt)

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapour to accumulate in low or confined areas.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Section 11. Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure
2-methoxy-1-methylethyl acetate	LD50 Dermal	Rat	>5000 mg/kg	-
Aliphatic polyisocyanate.	LD50 Oral	Rat - Female	>5000 mg/kg	-
	LC50 Inhalation Dusts and mists	Rat	2.18 mg/l	4 hours
	LD50 Dermal	Rabbit - Male, Female	>2000 mg/kg	-
	LD50 Dermal	Rat - Male, Female	>2000 mg/kg	-
n-butyl acetate	LD50 Oral	Rat	>5000 mg/kg	-
	LC50 Inhalation Vapour	Rat	>21.1 mg/l	4 hours
	LD50 Dermal	Rabbit	>14112 mg/kg	-
	LD50 Oral	Rat	10760 mg/kg	-
Aliphatic polyisocyanate 2.	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours
	LD50 Oral	Rat	>14000 mg/kg	-
xylene	LC50 Inhalation Vapour	Rat	27.6 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>2000 mg/kg	-
Solvent naphtha (petroleum), light arom.	LC50 Inhalation Vapour	Rat	>6193 mg/l	4 hours
	LD50 Dermal	Rabbit	>3160 mg/kg	-
1,2,4-trimethylbenzene ethylbenzene	LD50 Oral	Rat	3492 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
	LC50 Inhalation Vapour	Rat	>9.6 mg/l	4 hours
	LD50 Dermal	Rabbit	>15000 mg/kg	-
	LD50 Oral	Rat	>3500 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Aliphatic polyisocyanate.	Skin - Mild irritant	Rabbit	-	4 hours	-
	Eyes - Mild irritant	Rabbit	-	-	-
xylene	Skin - Mild irritant	Rat	-	8 hours 60 microliters	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Moderate irritant	Rabbit	-	100 Percent	-
	Eyes - Mild irritant	Rabbit	-	87 milligrams	-
ethylbenzene	Eyes - Severe irritant	Rabbit	-	24 hours 5 milligrams	-
	Eyes - Severe irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 15 milligrams	-
	Skin - Mild irritant	Rabbit	-	-	-

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
Aliphatic polyisocyanate.	skin	Mouse	Sensitising
	skin	Guinea pig	Sensitising

Mutagenicity

Product/ingredient name	Test	Experiment	Result
Aliphatic polyisocyanate.	OECD 471 Bacterial Reverse Mutation Test	Experiment: In vitro Subject: Bacteria Metabolic activation: +/-	Negative
	OECD 476 In vitro Mammalian Cell Gene Mutation Test	Experiment: In vitro Subject: Mammalian-Animal Metabolic activation: +/-	Negative

Carcinogenicity

Not available.

Section 11. Toxicological information

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
Aliphatic polyisocyanate.	Category 3	Not applicable.	Respiratory tract irritation
n-butyl acetate	Category 3	Not applicable.	Narcotic effects
Aliphatic polyisocyanate 2.	Category 3	Not applicable.	Respiratory tract irritation
xylene	Category 3	Not applicable.	Respiratory tract irritation
Solvent naphtha (petroleum), light arom.	Category 3	Not applicable.	Respiratory tract irritation and Narcotic effects
1,2,4-trimethylbenzene	Category 3	Not applicable.	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
xylene	Category 2	Not determined	Not determined

Aspiration hazard

Name	Result
xylene	ASPIRATION HAZARD - Category 1
Solvent naphtha (petroleum), light arom.	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : May cause respiratory irritation.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : Adverse symptoms may include the following:
nausea or vomiting

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Section 11. Toxicological information

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Product/ingredient name	Result	Species	Dose	Exposure
Aliphatic polyisocyanate.	Sub-chronic NOAEL Inhalation Dusts and mists	Rat - Male, Female	3.3 mg/m ³	90 days; 6 hours per day

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.

Mutagenicity : No known significant effects or critical hazards.

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Dermal	17405.1 mg/kg
Inhalation (vapours)	27.21 mg/l

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
2-methoxy-1-methylethyl acetate	Acute EC50 >1000 mg/l	Algae - Pseudokirchnerella subcapitata	96 hours
Aliphatic polyisocyanate.	Acute EC50 408 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 134 mg/l	Fish - Oncorhynchus mykiss	96 hours
	Acute EC50 >1000 mg/l	Algae - Scenedesmus subspicatus	72 hours
n-butyl acetate	Acute EC50 >100 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 >100 mg/l	Fish - Danio rerio	96 hours
	Acute EC50 397 mg/l	Algae - Selenastrum capricornutum	72 hours
Aliphatic polyisocyanate 2.	Acute EC50 44 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 32 mg/l	Crustaceans - Artemia salina	48 hours
	Acute LC50 18 mg/l	Fish - Pimephales promelas	96 hours
	Acute NOEC 200 mg/l	Algae	72 hours
	Acute EC50 >100 mg/l	Daphnia	48 hours
xylene	Acute EC50 >100 mg/l	Fish	96 hours
	Acute EC50 1 to 10 mg/l	Algae	72 hours
	Acute EC50 1 to 10 mg/l	Daphnia - Daphnia magna	48 hours
Solvent naphtha (petroleum), light arom.	Acute LC50 1 to 10 mg/l	Fish	96 hours
	Acute EC50 2.9 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 3.2 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 9.2 mg/l	Fish - Oncorhynchus mykiss	96 hours

Section 12. Ecological information

1,2,4-trimethylbenzene ethylbenzene	Acute NOEC >1 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 1 to 10 mg/l	Fish	96 hours
	Acute EC50 >1.8 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 >10 mg/l	Fish - Pimephales promelas	96 hours

Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
2-methoxy-1-methylethyl acetate	OECD 302B Inherent Biodegradability: Zahn-Wellens/ EMPA Test	100 % - 28 days	-	-
Aliphatic polyisocyanate. n-butyl acetate	OECD 301F Ready Biodegradability - Manometric Respirometry Test	83 % - 28 days	-	-
	EU 67/548/EEC ANNEX V, C.4.E.	1 % - Not readily - 28 days	-	-
Aliphatic polyisocyanate 2.	OECD 301D Ready Biodegradability - Closed Bottle Test	>80 % - 5 days	-	-
	OECD 302C Inherent Biodegradability: Modified MITI Test (II)	5 % - 28 days	-	-
Solvent naphtha (petroleum), light arom.	OECD 301F Ready Biodegradability - Manometric Respirometry Test	1 % - 28 days	-	-
	-	78 % - Readily - 28 days	-	Fresh water

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2-methoxy-1-methylethyl acetate	-	-	Readily
Aliphatic polyisocyanate. n-butyl acetate	Fresh water 7.7 days, 23°C	-	Not readily Readily
Aliphatic polyisocyanate 2.	-	-	Not readily
Solvent naphtha (petroleum), light arom.	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
2-methoxy-1-methylethyl acetate	1.2	-	low
Aliphatic polyisocyanate. n-butyl acetate	5.54 2.3	367.7 -	low low
xylene	3.12	8.1 to 25.9	low
1,2,4-trimethylbenzene	3.63	243	low
ethylbenzene	3.6	-	low

Section 12. Ecological information

Mobility in soil





Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spill material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	ADG	ADR/RID	IMDG	IATA
UN number	UN1263	UN1263	UN1263	UN1263
UN proper shipping name	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL	Paint related material
Transport hazard class(es)	3 	3 	3 	3 
Packing group	III	III	III	III
Environmental hazards	No.	No.	No.	No.
Additional information	<p>Hazchem code •3Y</p> <p>Special provisions 163, 223</p>	<p>Hazard identification number 30</p> <p>Limited quantity 5 L</p> <p>Special provisions 163, 640E, 650</p> <p>Tunnel code (D/E)</p>	<p>Emergency schedules (EmS) F-E, _S-E_</p> <p>Special provisions 163, 223, 955</p>	<p>Passenger and Cargo Aircraft Quantity limitation: 60 L Packaging instructions: 355 Cargo Aircraft Only Quantity limitation: 220 L Packaging instructions: 366 Limited Quantities - Passenger Aircraft Quantity limitation: 10 L Packaging instructions: Y344</p> <p>Special provisions</p>

Section 14. Transport information

A3, A72

Special precautions for user : **Transport within user's premises**: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to Annex II of Marpol and the IBC Code : Not available.

Section 15. Regulatory information

Standard Uniform Schedule of Medicine and Poisons

Not regulated.

Model Work Health and Safety Regulations - Scheduled Substances

No listed substance

Australia inventory (AICS) : All components are listed or exempted.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

International lists

National inventory

- Canada** : All components are listed or exempted.
- China** : All components are listed or exempted.
- Europe** : All components are listed or exempted.
- Japan** : **Japan inventory (ENCS)**: Not determined.
Japan inventory (ISHL): Not determined.
- Malaysia** : Not determined.
- New Zealand** : All components are listed or exempted.
- Philippines** : All components are listed or exempted.
- Republic of Korea** : All components are listed or exempted.
- Taiwan** : All components are listed or exempted.
- Turkey** : All components are listed or exempted.
- United States** : All components are listed or exempted.

Section 16. Any other relevant information

History

Date of printing	: 06/06/2017
Date of issue/Date of revision	: 05/06/2017
Date of previous issue	: No previous validation
Version	: 2
Key to abbreviations	: ADG = Australian Dangerous Goods ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) NOHSC = National Occupational Health and Safety Commission SUSMP = Standard Uniform Schedule of Medicine and Poisons UN = United Nations

Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 3	On basis of test data
SKIN CORROSION/IRRITATION - Category 2	Calculation method
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A	Calculation method
SKIN SENSITISATION - Category 1	Calculation method
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Respiratory tract irritation) - Category 3	Calculation method
ASPIRATION HAZARD - Category 1	Calculation method
LONG-TERM AQUATIC HAZARD - Category 3	Calculation method

References : Not available.

✔ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.