

SAFETY DATA SHEET



SP4796 HS Clear Coat 2:1

Section 1. Identification

Product name : SP4796 HS Clear Coat 2:1

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Use in coatings - Clearcoat

Supplier

Manufacturer : Valspar b.v.
Zuiveringweg 89
8243 PE Lelystad
The Netherlands
tel: +31 (0)320 292200
fax: +31 (0)320 292201

Emergency telephone number : Call: +31 (0)320 292200 (during daytime)

Supplier's details : DBNZ Coatings Limited
6 Killarney Lane
Hamilton 3243
NEW ZEALAND
T: +64 7847 0933
F: +64 7847 0932
E: info@dbnz.co.nz

Emergency telephone number (with hours of operation) : New Zealand Poisons Information Centre: 0800 764766 (24 hrs)

e-mail address of person responsible for this SDS : info.nl@valspar.com

Section 2. Hazards identification

HSNO Classification : 3.1 - FLAMMABLE LIQUIDS - Category C
6.1 - ACUTE TOXICITY (oral) - Category E
6.3 - SKIN IRRITATION - Category A
6.4 - EYE IRRITATION - Category A (Irritant)
6.5 - SENSITIZATION - Category B (Skin)
6.7 - CARCINOGENICITY - Category B
6.8 - REPRODUCTIVE AND DEVELOPMENTAL TOXICITY (Fertility) - Category B
6.8 - REPRODUCTIVE AND DEVELOPMENTAL TOXICITY (Unborn child) - Category B
6.9 - SPECIFIC TARGET ORGAN TOXICITY (SINGLE OR REPEATED EXPOSURE) - Category B
9.1 - AQUATIC ECOTOXICITY - Category D
9.3 - TERRESTRIAL VERTEBRATE ECOTOXICITY - Category C

This material is classified as hazardous according to criteria in the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001 and has been classified according to the Hazardous Substances (Classifications) Regulations 2001.

This material is classified as DANGEROUS GOODS according to criteria in New Zealand Standard 5433:2012 Transport of Dangerous Goods on Land.

GHS label elements

Signal word : Warning

Section 2. Hazards identification

Hazard statements : Flammable liquid and vapour.
May be harmful if swallowed.
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
Suspected of causing cancer.
Suspected of damaging fertility or the unborn child.
May cause damage to organs.
Harmful to aquatic life.
Harmful to terrestrial vertebrates.

Precautionary statements

Prevention : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves. Wear eye/face protection. Keep away from ignition sources such as heat/sparks/open flame. - No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Avoid release to the environment. Do not breathe vapour or spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

Response : IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Take off contaminated clothing and wash before reuse. Rinse skin with water/shower. Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician. Get medical advice/attention.

Storage : Store locked up. Store in a well-ventilated place. Keep cool.

Disposal : Dispose of contents and container in accordance with all local, regional, national and international regulations.

Symbol :



Other hazards which do not result in classification : None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	% (w/w)	CAS number
xylene	12.5 - 25	1330-20-7
n-butyl acetate	5 - 12.5	123-86-4
2-methoxy-1-methylethyl acetate	5 - 12.5	108-65-6
ethylbenzene	1 - 5	100-41-4
isobutyl acetate	1 - 5	110-19-0
4-methylpentan-2-one	1 - 5	108-10-1
ethyl 3-ethoxypropionate	1 - 5	763-69-9
Solvent naphtha (petroleum), light arom.	1 - 5	64742-95-6
1,2,4-trimethylbenzene	1 - 5	95-63-6
Hydroxyphenyl-benzotriazole derivate I	0 - 1	104810-48-2
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	0 - 1	41556-26-7
Hydroxyphenyl-benzotriazole derivate II	0 - 1	104810-47-1
methyl methacrylate	0 - 1	80-62-6
2-hydroxyethyl methacrylate	0 - 1	868-77-9
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	0 - 1	82919-37-7

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Section 3. Composition/information on ingredients

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Inhalation** : No known significant effects or critical hazards.
- Ingestion** : May be harmful if swallowed.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Eye contact** : Causes serious eye irritation.

Over-exposure signs/symptoms

- Inhalation** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Skin** : Adverse symptoms may include the following:
irritation
redness
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Eyes** : Adverse symptoms may include the following:
pain or irritation
watering
redness

Indication of immediate medical attention and special treatment needed, if necessary

- Specific treatments** : Not available.
- Notes to physician** : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Section 4. First aid measures

- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media

- Suitable** : Use dry chemical, CO₂, water spray (fog) or foam.

- Not suitable** : Do not use water jet.

- Specific hazards arising from the chemical** : Flammable liquid and vapour. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. This material is harmful to aquatic life. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

- Hazchem code** : 3Y

- Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

- Personal precautions, protective equipment and emergency procedures** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flames, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
xylene	NZ OSH (New Zealand, 2/2013). Notes: See Notice of Intended Changes. WES-TWA: 217 mg/m ³ , 0 times per shift, 8 hours. WES-TWA: 50 ppm, 0 times per shift, 8 hours.
n-butyl acetate	NZ OSH (New Zealand, 2/2013). WES-TWA: 150 ppm 8 hours. WES-TWA: 713 mg/m ³ 8 hours. WES-STEL: 950 mg/m ³ 15 minutes. WES-STEL: 200 ppm 15 minutes.
2-methoxy-1-methylethyl acetate	EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin. STEL: 548 mg/m ³ 15 minutes. TWA: 50 ppm 8 hours. TWA: 274 mg/m ³ 8 hours. STEL: 100 ppm 15 minutes.
ethylbenzene	NZ OSH (New Zealand, 2/2013). WES-STEL: 543 mg/m ³ 15 minutes. WES-STEL: 125 ppm 15 minutes. WES-TWA: 434 mg/m ³ 8 hours. WES-TWA: 100 ppm 8 hours.
isobutyl acetate	NZ OSH (New Zealand, 2/2013). WES-TWA: 713 mg/m ³ 8 hours. WES-TWA: 150 ppm 8 hours.
4-methylpentan-2-one	NZ OSH (New Zealand, 2/2013). WES-STEL: 307 mg/m ³ 15 minutes. WES-STEL: 75 ppm 15 minutes.

Section 8. Exposure controls/personal protection

1,2,4-trimethylbenzene

methyl methacrylate

WES-TWA: 205 mg/m³ 8 hours.

WES-TWA: 50 ppm 8 hours.

ACGIH TLV (United States, 3/2016).TWA: 123 mg/m³ 8 hours.

TWA: 25 ppm 8 hours.

NZ OSH (New Zealand, 2/2013). Absorbed through skin. Skin sensitiser.WES-STEL: 416 mg/m³ 15 minutes.

WES-STEL: 100 ppm 15 hours.

WES-TWA: 208 mg/m³ 8 hours.

WES-TWA: 50 ppm 8 hours.

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
- Individual protection measures**
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: EN 405:2001 + A1:2009 organic vapour (Type A) and particulate filter FFA2P3 R D
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): Recommended EN 374 polyvinyl alcohol (PVA) Viton® >= 0.7 mm
< 1 hour (breakthrough time): Conditionally suitable materials for protective gloves; EN 374: Nitrile rubber - NBR (>= 0.35 mm). Only suitable as splash protection. Only suitable for brief exposure. In the event of contamination, change protective gloves immediately.
- Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. Recommended: chemical splash goggles and/or face shield.
- Skin protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Recommended: Cotton or cotton/synthetic overalls or coveralls are normally suitable.

Section 9. Physical and chemical properties

Appearance

Physical state	: Liquid.
Colour	: Clear.
Odour	: Not available.
Odour threshold	: Not available.
pH	: Not available.
Melting point	: Not available.
Boiling point	: >100°C (>212°F)
Flash point	: Closed cup: 27°C (80.6°F)
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Vapour pressure	: Not available.
Vapour density	: Not available.
Relative density	: 0.98
Solubility	: Insoluble in the following materials: cold water and hot water.
Partition coefficient: n-octanol/water	: Not available.
Auto-ignition temperature	: 350°C (662°F)
Decomposition temperature	: Not available.
Viscosity	: Kinematic (40°C (104°F)): 0.06 cm ² /s (6 cSt)

Aerosol product

Type of aerosol	: Not applicable.
Heat of combustion	: Not available.
Ignition distance	: Not applicable.
Enclosed space ignition - Time equivalent	: Not applicable.
Enclosed space ignition - Deflagration density	: Not applicable.
Flame height	: Not applicable.
Flame duration	: Not applicable.

Section 10. Stability and reactivity

Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on likely routes of exposure

- Inhalation** : No known significant effects or critical hazards.
- Ingestion** : May be harmful if swallowed.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Eye contact** : Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

- Inhalation** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
reduced foetal weight
increase in foetal deaths
skeletal malformations
- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
xylene	LC50 Inhalation Vapour	Rat	27.6 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
n-butyl acetate	LD50 Oral	Rat	>2000 mg/kg	-
	LC50 Inhalation Vapour	Rat	>21.1 mg/l	4 hours
	LD50 Dermal	Rabbit	>14112 mg/kg	-
2-methoxy-1-methylethyl acetate	LD50 Oral	Rat	10760 mg/kg	-
	LD50 Dermal	Rat	>5000 mg/kg	-
ethylbenzene	LD50 Oral	Rat - Female	>5000 mg/kg	-
	LC50 Inhalation Vapour	Rat	>9.6 mg/l	4 hours
	LD50 Dermal	Rabbit	>15000 mg/kg	-
isobutyl acetate	LD50 Oral	Rat	>3500 mg/kg	-
	LD50 Dermal	Rabbit	>17400 mg/kg	-
	LD50 Oral	Rat	13400 mg/kg	-
4-methylpentan-2-one	LC50 Inhalation Vapour	Rat	8.2 to 16.4 mg/l	4 hours
	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	2080 mg/kg	-
ethyl 3-ethoxypropionate	LD50 Dermal	Rabbit - Male	4080 mg/kg	-
	LD50 Oral	Rat - Female	>4.3 g/kg	-
Solvent naphtha (petroleum), light arom.	LC50 Inhalation Vapour	Rat	>6193 mg/l	4 hours
	LD50 Dermal	Rabbit	>3160 mg/kg	-
1,2,4-trimethylbenzene	LD50 Oral	Rat	3492 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
	LD50 Dermal	Rat	>2000 mg/kg	-
Hydroxyphenyl-benzotriazole derivate I	LD50 Oral	Rat	>5000 mg/kg	-
	LD50 Oral	Rat	>3230 mg/kg	-
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	LD50 Oral	Rat	>5000 mg/kg	-
	LD50 Oral	Rat	>3230 mg/kg	-
Hydroxyphenyl-benzotriazole derivate II	LD50 Dermal	Rat	>2000 mg/kg	-

Section 11. Toxicological information

methyl methacrylate	LD50 Oral LC50 Inhalation Vapour	Rat Rat - Male, Female	>5000 mg/kg 29.8 mg/l	- 4 hours
2-hydroxyethyl methacrylate	LD50 Dermal LD50 Oral LD50 Dermal	Rabbit Rat Rabbit	5000 mg/kg 7872 mg/kg >3000 mg/kg	- - -
methyl 1,2,2,6, 6-pentamethyl-4-piperidyl sebacate	LD50 Oral LD50 Oral	Rat Rat	5050 mg/kg >3230 mg/kg	- -

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
xylene	Skin - Mild irritant	Rat	-	8 hours 60 microliters	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Moderate irritant	Rabbit	-	100 Percent	-
	Eyes - Mild irritant	Rabbit	-	87 milligrams	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 milligrams	-
ethylbenzene	Eyes - Severe irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 15 milligrams	-
isobutyl acetate	Eyes - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Mild irritant	Rabbit	-	500 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
4-methylpentan-2-one	Eyes - Moderate irritant	Rabbit	-	24 hours 100 microliters	-
	Eyes - Severe irritant	Rabbit	-	40 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
ethyl 3-ethoxypropionate	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-

Sensitisation

Not available.

Potential chronic health effects

- General** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.
- Skin contact** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Eye contact** : No known significant effects or critical hazards.
- Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : Suspected of damaging the unborn child.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : Suspected of damaging fertility.

Chronic toxicity

Not available.

Carcinogenicity

Section 11. Toxicological information

Not available.

Mutagenicity

Not available.

Teratogenicity

Not available.

Reproductive toxicity

Not available.

Specific target organ toxicity

Name	Category	Route of exposure	Target organs
xylene	Category B	Oral Inhalation	Not determined Not determined
ethylbenzene	Category B	Inhalation	Not determined
1,2,4-trimethylbenzene	Category B	Inhalation	Not determined
methyl methacrylate	Category B	Inhalation	Not determined

Aspiration hazard

Name
Solvent naphtha (petroleum), light arom.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	2374 mg/kg
Dermal	7596.7 mg/kg
Inhalation (vapours)	73.78 mg/l

Section 12. Ecological information

Ecotoxicity : This material is harmful to aquatic life.

Aquatic and terrestrial toxicity

Product/ingredient name	Result	Species	Exposure
xylene	Acute EC50 1 to 10 mg/l	Algae	72 hours
	Acute EC50 1 to 10 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 1 to 10 mg/l	Fish	96 hours
n-butyl acetate	Acute EC50 397 mg/l	Algae - Selenastrum capricornutum	72 hours
	Acute EC50 44 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 32 mg/l	Crustaceans - Artemia salina	48 hours
	Acute LC50 18 mg/l	Fish - Pimephales promelas	96 hours
	Acute NOEC 200 mg/l	Algae	72 hours
2-methoxy-1-methylethyl acetate	Acute EC50 >1000 mg/l	Algae - Pseudokirchnerella subcapitata	96 hours
	Acute EC50 408 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 134 mg/l	Fish - Oncorhynchus mykiss	96 hours
ethylbenzene	Acute EC50 >1.8 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 >10 mg/l	Fish - Pimephales promelas	96 hours
4-methylpentan-2-one	EC50 400 mg/l	Algae	96 hours
	EC50 >200 mg/l	Daphnia - Daphnia magna	48 hours
	LC50 >179 mg/l	Fish - Danio rerio	96 hours
ethyl 3-ethoxypropionate	Acute EC50 114.86 mg/l	Aquatic plants - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 785 to 970 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 88 mg/l	Fish - Pimephales promelas	96 hours
Solvent naphtha (petroleum), light arom.	Acute EC50 2.9 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours

Section 12. Ecological information

1,2,4-trimethylbenzene Hydroxyphenyl-benzotriazole derivate I	Acute EC50 3.2 mg/l Acute LC50 9.2 mg/l Acute NOEC >1 mg/l	Daphnia - Daphnia magna Fish - Oncorhynchus mykiss Algae - Pseudokirchneriella subcapitata	48 hours 96 hours 72 hours
	Acute EC50 1 to 10 mg/l Acute LC50 2.8 mg/l	Fish Fish	96 hours 96 hours
bis(1,2,2,6,6-pentamethyl- 4-piperidyl) sebacate	Acute EC50 0.22 mg/l	Algae	72 hours
	Acute LC50 0.9 mg/l Acute NOEC 6.3 mg/l Acute LC50 2.8 mg/l	Fish Daphnia Fish	96 hours 21 days 96 hours
Hydroxyphenyl-benzotriazole derivate II methyl methacrylate	Acute EC50 >110 mg/l Fresh water	Algae - Pseudokirchnerella subcapitata	72 hours
	Acute EC50 69 mg/l Fresh water Acute LC50 130 mg/l Fresh water Acute NOEC 49 mg/l Fresh water	Daphnia - Daphnia magna Fish - Pimephales promelas Algae - Pseudokirchnerella subcapitata	48 hours 96 hours 72 hours
2-hydroxyethyl methacrylate	Chronic NOEC 37 mg/l Fresh water Chronic NOEC 9.4 mg/l Fresh water Acute EC50 345 mg/l	Daphnia - Daphnia magna Fish - Danio rerio Algae - Selenastrum capricornutum	21 days 35 days 72 hours
	Acute EC50 210 mg/l Acute EC50 380 mg/l Acute LC50 227 mg/l Acute NOEC 160 mg/l	Crustaceans Daphnia Fish Algae - Selenastrum capricornutum	48 hours 48 hours 96 hours 72 hours
methyl 1,2,2,6, 6-pentamethyl-4-piperidyl sebacate	Acute NOEC 25 mg/l Chronic NOEC 24.1 mg/l Acute EC50 0.22 mg/l	Fish - Oryzias latipes Daphnia Algae	14 days 21 days 72 hours
	Acute LC50 0.9 mg/l Acute NOEC 6.3 mg/l	Fish Daphnia	96 hours 21 days

Persistence/degradability

Product/ingredient name	Test	Result	Dose	Inoculum
n-butyl acetate	OECD 301D Ready Biodegradability - Closed Bottle Test	>80 % - 5 days	-	-
2-methoxy-1-methylethyl acetate	OECD 302B Inherent Biodegradability: Zahn-Wellens/ EMPA Test	100 % - 28 days	-	-
	OECD 301F Ready Biodegradability - Manometric Respirometry Test	83 % - 28 days	-	-
ethyl 3-ethoxypropionate	OECD 301B Ready Biodegradability - CO2 Evolution Test	100 % - Readily - 18 days	-	-
Solvent naphtha (petroleum), light arom.	-	78 % - Readily - 28 days	-	Fresh water
2-hydroxyethyl methacrylate	OECD 301E Ready	98 % - Readily - 28 days	-	-

Section 12. Ecological information

	Biodegradability - Modified OECD Screening Test OECD 301C Ready	92 to 100 % - Readily - 14 days	-	-
	Biodegradability - Modified MITI Test (I) OECD 301D Ready	84 % - Readily - 28 days	-	-
	Biodegradability - Closed Bottle Test			

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
n-butyl acetate	-	-	Readily
2-methoxy-1-methylethyl acetate	-	-	Readily
4-methylpentan-2-one	-	-	Readily
ethyl 3-ethoxypropionate	-	-	Readily
Solvent naphtha (petroleum), light arom.	-	-	Readily
2-hydroxyethyl methacrylate	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogP _{ow}	BCF	Potential
xylene	3.12	8.1 to 25.9	low
n-butyl acetate	2.3	-	low
2-methoxy-1-methylethyl acetate	1.2	-	low
ethylbenzene	3.6	-	low
isobutyl acetate	2.3	-	low
4-methylpentan-2-one	1.9	-	low
ethyl 3-ethoxypropionate	1.47	-	low
1,2,4-trimethylbenzene	3.63	243	low
methyl methacrylate	1.38	-	low
2-hydroxyethyl methacrylate	0.42	-	low

Mobility in soil







Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
New Zealand Class	UN1263	PAINT	3	III		Hazchem code 3Y Special provisions 163, 223
ADG Class	UN1263	PAINT	3	III		Hazchem code •3Y Special provisions 163, 223
UN Class	UN1263	PAINT	3	III		Special provisions 163, 223
ADR/RID Class	UN1263	PAINT	3	III		Hazard identification number 30 Limited quantity 5 L Special provisions 163, 640E, 650 Tunnel code (D/E)
IATA Class	UN1263	Paint	3	III		Passenger and Cargo Aircraft Quantity limitation: 60 L Packaging instructions: 355 Cargo Aircraft Only Quantity limitation: 220 L Packaging instructions: 366 Limited Quantities - Passenger Aircraft Quantity limitation: 10 L Packaging instructions: Y344 Special provisions A3, A72
IMDG Class	UN1263	PAINT	3	III		Emergency schedules (EmS) F-E, _S-E_ Special provisions 163, 223, 955

PG* : Packing group

Section 15. Regulatory information

- New Zealand Inventory of Chemicals (NZIoC)** : All components are listed or exempted.
- HSNO Approval Number** : HSR002669
- HSNO Group Standard** : Surface Coatings and Colourants
- HSNO Classification** : 3.1 - FLAMMABLE LIQUIDS - Category C
 6.1 - ACUTE TOXICITY (oral) - Category E
 6.3 - SKIN IRRITATION - Category A
 6.4 - EYE IRRITATION - Category A (Irritant)
 6.5 - SENSITIZATION - Category B (Skin)
 6.7 - CARCINOGENICITY - Category B
 6.8 - REPRODUCTIVE AND DEVELOPMENTAL TOXICITY (Fertility) - Category B
 6.8 - REPRODUCTIVE AND DEVELOPMENTAL TOXICITY (Unborn child) - Category B
 6.9 - SPECIFIC TARGET ORGAN TOXICITY (SINGLE OR REPEATED EXPOSURE) - Category B
 9.1 - AQUATIC ECOTOXICITY - Category D
 9.3 - TERRESTRIAL VERTEBRATE ECOTOXICITY - Category C

Australia inventory (AICS) : All components are listed or exempted.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

International lists

National inventory

- Australia** : All components are listed or exempted.
- Canada** : All components are listed or exempted.
- China** : All components are listed or exempted.
- Europe** : All components are listed or exempted.
- Japan** : **Japan inventory (ENCS)**: All components are listed or exempted.
Japan inventory (ISHL): Not determined.
- Malaysia** : Not determined.
- Philippines** : All components are listed or exempted.
- Republic of Korea** : All components are listed or exempted.
- Taiwan** : All components are listed or exempted.
- Turkey** : Not determined.
- United States** : All components are listed or exempted.

Section 16. Other information

History

Date of printing	: 06/06/2017
Date of issue/Date of revision	: 06/06/2017
Date of previous issue	: 05/06/2017
Version	: 2
Key to abbreviations	: ADG = Australian Dangerous Goods ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail UN = United Nations
References	: Not available.

✔ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.