

GENERAL INFORMATION

SP6499 Silicone Remover Standard Silicon Remover.

MIXING RATIO



-

GUN SET UP



	NOZZLE (MM)	AIR PRESSURE (BAR / PSI)
HVLP	-	-
HE	-	-

APPLICATION



-

FLASH OFF AND DRY TIMES



	AIR DRY 20°C / 68°F	FORCED DRY 60°C / 140°F
Flash off	-	Flash off -
Dust free	-	Dust free -
Dry to handle	-	Dry to handle -
Dry to tape	-	Dry to tape -
Dry to sand	-	Dry to sand -
Dry to polish	-	Dry to polish -

SUBSTRATES



Bare Steel, old and new paint systems.

POT LIFE AT 20°C / 68°F



-

COMPONENTS



-

ADDITIVES



-

SURFACE PREPARATION



-



NEXT LAYER

-

EU REGULATIONS

VOC Code		2004/42/IIIB(a)(850)759
Product sub category (according directive 2004/42/EC) and max VOC content (ISO 11980-1/2) of the ready to use product.		IIIB/a. Preparatory and cleaning - Preparatory. EU limit values: 850g/l. (2007) This product contains a maximum of 759 g/l VOC.
Chemical Base	Mix of organic solvents and thinners	
Physical Properties	Viscosity	-
	Specific gravity (kg/l)	0.792
	Flash Point Closed Cup	9°C (48,2°F)
	Vol. % Solids	-
	Economy	0
	Gloss	-
	Colour	-



SP6499

Silicone Remover



PROTECTION



Use suitable respiratory protection (we recommend the use of a fresh air supply respirator).

CLEAN UP



STORAGE/SHELF LIFE

Minimum 2 years; (Under normal storage conditions 10°C - 30°C / 50°F - 90°F) (unopened container).



NOTES